



easy 6000 GCD

easy 6000 GCD

drum machines

- High impact design, co-ordinating with Hot & Cold machines
- External surface linear and smooth for easier cleaning
- 32 - bit electronics with USB 2.0 HOST
- Compact cooling unit easily extractable (patent pending)
- Visual version with backlit products label holder and LCD prices display
- Side-mounted air circulator (patented)
- Extractable drums for easier products reloading
- Door with anti-thief side bar, 3 locking points and re-programmable lock
- Internal LED lighting
- Low energy consumption
- Automatic opening and closing delivery doors with variable timing
- Graphic colour display 480 x 272 pixel with the possibility of personalised slide shows and / or visualization of supplementary information (ex: product ingredients and nutritional value)
- 8 drums with 120 mm height, with drum compartments from 4 - 6 - 8 - 12 - 16 - 24 - 48
- Programming, cloning, and Audit functions using a standard USB Pen Drive

Version T

- Interactive user interface with 7" TABLET
- Integrated WIFI connection
- Configured for dongle key internet connection



Easy 6000 GCD



Easy 6000 T



PowerLED, high illumination efficiency and low energy consumption



Automatic opening and closing delivery doors



Compact cooling unit easily extractable



Extractable drums

General Features		Easy 6000
Height	mm	1830
Width	mm	910
Depth	mm	790
Dimensions with door open	mm	1660
Weight	Kg	315
Surfaces and door parts		metal
Vend mode		FIFO and shopper
Antitheft profile		yes
Power	V / Hz	230 / 50
EVA-EMP consumption (idle mode)	Wh / h	346
Temperature	C°	minimum +3° with refrigeration safety
Protocol		MDB Executive BDV
Colour		black RAL 9005 & aluminium

Fas International Spa

Via Lago di Vico, 60
36015 Schio · Vicenza · Italy
T +39 0445 502011

F +39 0445 502.010
info@fas.it
www.fas.it

