



YOUNG GCD

- 6 spirals drawer
- Patented, energy-saving, slide-in/slide-out refrigeration unit that can be replaced quickly
- Patented lateral refrigeration ventilation for energy savings, condensation and optimal homogenization of temperatures
- 32 -bit electronics
- Power Led illumination with Energy Saving
- Programming, cloning, and Audit functions using a standard USB pen drive
- Graphic colour display 480x272 pixel with the possibility of a personalised slide shows and/or visualization of supplementary information (ex: product ingredients and nutritional value)
- Drawer Display Kit
- Rielda RS1 Lock
- **Easy Click System:** for configuring the machine quickly and easily without any need for technical instruments
- Configuration possibilities:
1T - 2T - 3T Snack + Drink + Food (183 version)
2T (170 version)
- Polyurethane foam insulation (CFC Free)
- Pre-cooling storage
- Reflector product photocells detectors



Young 183

Young 170



500T

Young FV 183



Easy Click system

Characteristics	YOUNG 170/183		YOUNG FV 170/183	
Height	mm	1700/1830		1700/1830
Width	mm	750		750
Depth	mm	790		790
Dimensions with door open	mm	1470		1470
Weigh	Kg	224/239		225/243
Surfaces and door parts		metal		metal
Antitheft profile		no		no
Power	V / Hz	230/50		230/50
Internal temperature - min	C°	+3°C with fridge safety on 3 bottom drawers		+3°C with fridge safety on 3 bottom drawers
Protocol		MDB/Executive		MDB/Executive
Standard colour		Profile: anodised extruded aluminium Surfaces: black - Ral 9005		Profile: anodised extruded aluminium Surfaces: black - Ral 9005

Fas International Spa
Via Lago di Vico, 60
36015 Schio · Vicenza · Italy
T +39 0445 502011

F +39 0445 502.010
info@fas.it
www.fas.it

